

SRD-1653D

16CH CIF (960H available) Real-time Coaxial DVR




Key Features

- 16CH CIF real-time DVR
- Max. resolution of 928 x 480 / 928 x 576
- Up to 480(NTSC) / 400(PAL)fps recording rate
- HDMI / VGA video output
- Max. 4 internal HDDs
- PTZ control via coaxial cable (Samsung CCVC, Pelco-C)
- DVD-RW, Smart phone support (Android / iOS)
- Enhanced Network Bandwidth up to 32Mbps

Dimensions

Unit : mm (inch)



		SRD-1653D
DISPLAY		
Video	Inputs	16 Composite video 0.5-1 Vpp, 75 ohm automatic termination
	Resolution	NTSC : 928 x 480, 704 x 480 / PAL : 928 x 576, 704 x 576
Live	Frame Rate	NTSC : 480fps / PAL : 400fps
	Resolution	NTSC : 928 x 480, 704 x 480 / PAL : 928 x 576, 704 x 576
	Multi Screen Display	1 / 4 / 7 / 9 / 13 / 16 / 16A / Sequence / PIP
PERFORMANCE		
Operating System	Embedded	Linux
	Compression	H.264
Recording	Record Rate	NTSC : Up to 120fps@928 x 480 / PAL : Up to 100fps@928 x 576 NTSC : Up to 120fps@704 x 480 / PAL : Up to 100fps@704 x 576 NTSC : Up to 240fps@704 x 240 / PAL : Up to 200fps@704 x 288 NTSC : Up to 480fps@352 x 240 / PAL : Up to 400fps@352 x 288
	Mode	NTSC : Manual, Schedule (Continuous / Event), Event (Pre / Post), Time lapse (1 ~ 30 fps) PAL : Manual, Schedule (Continuous / Event), Event (Pre / Post), Time lapse (1 ~ 25 fps)
	Event	Video loss, Motion (Level 1 ~ 10), Alarm, Tampering (Level 1 ~ 3)
	Overwrite Modes	Selectable (Stop / Continuous)
	Pre-alarm	Up to 30sec (5, 10, 20, 30sec)
	Post-alarm	Up to 6hour (5, 10, 20, 30sec, 1, 3, 5, 10, 20min, 1, 2, 3, 4, 5, 6hour)
Search & Playback	Search Mode	Date/Time, Event, Back up, POS, Motion (*All search include preview function)
	Playback Function	Fast forward / backward (2x, 4x, 8x, 16x, 32x, 64x) *Backward play with i-frame only Slow forward / backward (1/2x, 1/4x, 1/8x) Step forward / backward (2x, 4x, 8x, 16x, 32x, 64x) *Backward play with i-frame only
Network (IPv4)	Transmission Speed	4CIF / 2CIF / CIF (NTSC : 120 / 240 / 480fps, PAL : 100 / 200 / 400fps)
	Bandwidth	Up to 32Mbps
	Bandwidth Control	Selectable
	Stream	H.264 (4CIF / 2CIF / CIF selectable)
	Max. Remote Users	Search 3 / Live unicast 10 / Live multicast 20
Smart Phone	Protocol Support	TCP/IP, DHCP, PPPoE, SMTP, NTP, HTTP, DDNS, RTP, RTSP, SNMP
	Monitoring	SmartViewer, Webviewer, SSM (CMS)
	Platform	Android, iOS
Storage	Internal HDD	Up to 4 SATA HDDs
	External (e-SATA Interface)	Up to 2 expansion bays (*Model : SVS-5R/5E)
Security	DVD Writer (Back up)	Yes
	USB (Back up)	2 USB ports
	File Format (Back up)	BU (DVR player), EXE (Include player), AVI
Security	Password Protection	1 Admin, 10 Group, 10 User per 1 group
	Data Authentication	Watermark
INTERFACE		
Monitors	VGA	1 VGA (1280 x 720, 1280 x 1024, 1920 x 1080)
	HDMI	1 HDMI (1280 x 720, 1280 x 1024, 1920 x 1080)
	Spot Composite	Digital spot (2CH) *Included OSD on screen, multi mode support (1CH)
Audio	Inputs / Output	16CH line in (Built-in 4CH, option : audio extension cable) / 1CH line out
	Compression	G.711
	Sampling Rate	8KHz
Alarm	Inputs / Output	Terminal 16 inputs (NO/NC) / Terminal 4 relay outputs (NO/NC), Rating : 30V DC / 2A, 250V AC / 0.25A
	Remote Notification	Notification via e-mail
Connections	Ethernet	1 RJ-45 10/100/1000 Base-T
	Serial Interface	RS-232/RS-485 for PTZ, Samsung system keyboard
	USB	USB 2.0, 2 ports (Front)
	eSATA	2 External SATA ports
	Application Support	Mouse, Remote controller
GENERAL	RS-485 Protocol	Samsung T/E, Pelco-D/P, Panasonic, Phillips, AD, DIAMOND, ERNA, KALATEL, VCL TP, VICON, ELMO, GE
	Coax Protocol	Samsung CCVC, Pelco-C
Electrical	Input Voltage / Current	100 ~ 240V AC ±10%, 50/60Hz, Auto ranging
	Power Consumption	Max. 60W (With 1x HDD)
	Operating Temperature	+0°C ~ +40°C (+32°F ~ +104°F)
Environmental	Operating Humidity	20% ~ 85% RH
	Dimensions (WxHxD)	440.0 x 88.0 x 246.8mm (17.32" x 3.46" x 9.72")
Mechanical	Weight (With hard disks)	Approx. 5.2Kg (11.46 lb)
	Rack Mount Kit	2ea
Language	English, French, German, Spanish, Italian, Russian, Polish, Czech, Turkish, Netherlands, Portuguese, Swedish, Danish, Rumania, Serbia, Croatia, Hungary, Greek, Finnish, Norwegian, Korean, Japanese, Chinese (Traditional), Thai, Taiwanese (25 Language)	

* The latest product information / specification can be found at www.samsungsecurity.com